

152-SERIES AQUA BORNE CERAMIC ACRYLIC SOFT GLOSS HOUSE PAINT

Aqua Borne Ceramic Soft Gloss House Paint provides long term durability against the harmful effects of sunlight, snow and rain. You can use it on wood, masonry, vinyl, aluminum siding, hardboard siding and be sure of receiving the very best protection while providing a beautiful luxurious look. An environmentally friendly product; low VOC, contains no toxic substances. Dries to a soft pleasing sheen. **Contains Ceramic Microspheres to keep the finish brighter and cleaner.**

USES: Exterior wood, hardboard, aluminum and vinyl siding and trim, masonry, brick, stucco and primed metal. For maximum durability, apply 2 coats over properly prepared previous coating or appropriate primer where recommended.

MATERIAL PREPARATION: Mix well before using. Thin sparingly if needed.

SURFACE PREPARATION: All surfaces should be cleaned of dust, dirt, grease and mildew. Use strong detergent or trisodium phosphate to clean previously painted surfaces, especially if chalky from weather exposure. Remove mildew with bleach solution. Scuff sand all glossy surfaces. Scrape or wire brush loose, flaking or crumbling paint, sand to a feather edge and prime if necessary. Caulk open construction joints. Counter sink nails, prime and fill with putty. Prime bare wood with quality primer. Prime all new hardboard (even factory pre-primed type) with oil/alkyd based primer. Clean all steel surfaces and prime with metal primer. Wash galvanized metal with solvent, scuff with steel wool or sandpaper and prime. The 152-series requires no primer over clean masonry surfaces.

APPLICATION: Avoid painting in hot, direct sun or in conditions of extreme humidity. Apply by brush, roller or spray. Apply full, even coats and always work to a wet edge. Do not apply when temperature of air is below 34°F or when temperature of air or surface may drop below 34°F within 24 hours.

152-series

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	White and bases
<u>60° GLOSS:</u>	20-30 range
<u>85° SHEEN:</u>	n/a
<u>VEHICLE:</u>	Acrylic resin emulsion, exterior type
<u>PIGMENTATION:</u>	Titanium dioxide (type III). Ground colors and tints use various light fast pigments free of heavy metals or other toxic materials.
<u>SOLVENT:</u>	Water and EPA exempt glycols. VOC 133g/L; 1.11 lbs/gal.
<u>FLAMMABILITY:</u>	n/a
<u>% TOTAL SOLIDS (WEIGHT):</u>	48 (152-49)
<u>% TOTAL SOLIDS (VOLUME):</u>	35
<u>VISCOSITY:</u>	90-95 KU
<u>THEORETICAL COVERAGE:</u>	300 sq.ft/gal=5.3 wet mils=1.9 dry mils 400 sq.ft/gal=4.0 wet mils=1.4 dry mils 500 sq.ft/gal=3.2 wet mils=1.1 dry mils
<u>RECOMMENDED COVERAGE:</u>	400 square feet per gallon
<u>WEIGHT PER GALLON:</u>	10.5 lbs.
<u>DRY, SET TO TOUCH:</u>	One hour
<u>DRY HARD:</u>	2 hours (recoat)
<u>CLEAN UP SOLVENT:</u>	Warm, soapy water
<u>TYPE OF CURE:</u>	Coalescence
<u>TINTING:</u>	Universal colorants